615

Electronic pressure switch Relative –1 to +600 bar Absolute 0 to 16 bar



EDITION 05/2001





FOR FINE PRESSURE AND FLOW MEASUREMENT



EDITION 05/2001

Technical overview

The type 615 electronic absolute and relative pressure switches measure pressure by means of highly resistant ceramic elements. An open collector (transistor) output accommodates loads up to 100 mA. Either an N/C or N/O contact may be used, and the upper and lower switching point can be freely selected in the range 5 to 100% fs. Various electrical and pressure connections are available to suit given applications.

Pressure types

Relative pressure (measurement of differential pressure to ambient pressure). Absolute pressure.

Overload

2x measuring range (fs)

Rupture pressure

3x measuring range (fs)

Accuracy

Repeatability < +/-0.5 % fs. Accuracy of switching point adjustments < 1 % fs.

Materials of housing in contact with the medium

Ceramic/Inox 1.4305 Ceramic / PVDF on request Max. pressure/overpressure see order code selection table «pressure ranges».

The distinct advantages

- Ideal for frequent switching cycles
- Long service life and long-term stability due to lack of moving parts (unlike mechanical pressure switches)
- Very low susceptibility to temperature
- Modular system for easy implementation of individual applications

Sealing material: optionally Viton, EPDM, NBR, silicone according to order code selection table.

Temperature influences

Medium and ambient temperature -15 °C to +80 °C Medium and ambient temperature -40 °C only with CR seal and on request. TC zero point < +/-0.05 % fs/ °C TC sensitivity typically < +/-0.02 % fs/ °C

Load cycle

< 50 Hz

Mechanical rating

Resistant to vibration up to 15 g.

Dynamic response

Suitable for static and dynamic measurements. Response time < 5 ms

Pressure connections

Inside thread G 1/4 Outside thread G 1/8, G 1/4, G 1/2 Connection fitting sealed at front or at back (option). 7/16-20 UNF / 1/4-18 NPT / 1/2-14 NPT See order code selection table.

Weight

Inside thread:	
G 1/4	200 grams
Outside thread:	
G 1/8 / 7/16-20 UNF	212 grams
G 1/4 / 1/4-18 NPT	245 grams
G 1/2 / 1/2-14 NPT	280 grams

Installation arrangement

Unrestricted.

Power supply

10 ... 33 VDC 24 VAC +/-15 %

Output

Open collector switch output for max. 100 mA at maximum supply voltage.

Short circuit proof and protected against polarity reversal. Each connection against other with max. +/- supply voltage.

Electromagnetic compatibility: CE conformity to EC directive 89/336 EEC (EMC) by application of harmonized standards EN 50081-1, EN 50081-2 and EN 50082-2.

Adjustment of switching points

The upper and lower switching point can be freely selected between 5 and 100% fs. Recommended spacing between upper and lower switching points: > 2% fs (factory-set at 5 and 100% unless switching point is specified).

Electrical connection / Protection class

Cable 1.5 meters, IP 67. Cable 1.5 meters, IP 65. Round plug connector DIN 41524, 3-pole, IP 65. Connector DIN 43650-A, IP 65.

Operation / Switch status indication

N/C contact: When pressure is applied ($p_0 \rightarrow p_{max}$) the collector will disconnect the applied load as soon as the upper switching point is reached. As the pressure falls ($p_{max} \rightarrow p_0$) the collector will connect the load as soon as the lower switching point is reached.

N/O contact: When pressure is applied ($p_0 \rightarrow p_{max}$) the collector will connect the applied load as soon as the upper switching point is reached. With a fall in pressure ($p_{max} \rightarrow p_0$) the collector will disconnect the load as soon as the lower switching point is reached.

Switch status indication: LED in DIN connector (see accessories).

Example: prs 20 bar. Upper switching point 12 bar. Lower switching point 8 bar.



A	B	c	-	 A – Outside thread G 1/4 B – Outside thread G 1/2 C – Inside thread G 1/4 D – Outside thread F – Cable connection 	
		G	T	IP 65 F – Female connec- tor DIN 43650-A G – Round plug connector IP 65 H – Mounting bracket	Versions

Order code select	ion table	EDITION 0)5/2001	615	Х	Х	Х	Χ	Х	Х	Χ	Х	Χ
				Relative pressure	9								
Pressure ranges ¹ (bar)	-1 0			Absolute pressure	9	0	0						
	-1 + 0.6				9	0	1						
	-1+ 1 -1 + 15				9		2 २						
	-1 + 3				9	ŏ	4						
	-1 + 5				9	0	5						
	-1 + 9				9	0	6						
	0 + 0.3					2	6		_	_			
	0 + 0.6						1						
	0 + 1.6					1	2						
	0 + 2.5					1	4						
	0 + 4					1	5						
	0 + 6					1	7		_	_			
	0 + 10 0 + 16					3	1						
	0 + 25				9	3	2						
	0 + 40				9	3	3						
	0 + 60				9	4	0						
	0 + 100				9	4	1						
	0 + 160 0 + 250				9	4	2 २						
	0 + 400 seal on	lv Viton			9	5	4	0					
	0 + 600 seal on	ly Viton (overpressure	e max. 1 00	0 bar)	9	5	5	0					
Sealing materials ²	FPM Fluoro-	elastomer (Viton)						0					
	EPDM Ethylen	ie propylene						1					
	NBR Nitrile I	butadiene						2	_				
		e polymer						2					
Switching points	Factory-set								0				
(specify on order form)	Not factory-set (only	/ IP 65)							1				
Switch contact	Normally open NP	'N non-floating								0			
Switch contact	Normally closed NP	'N non-floating								1			
	Normally open PN	P non-floating								2			
	Normally closed PN	P non-floating								3			
Electrical connections3	Cable 15 meters Pr	n 7	(Protection	a class IP 65)							0		
Electrical connections	Cable 15 meters Po	y / n 7	(Protection	n class IP 67)							2		
	Connector DIN 4365	0-A	(Protection	n class IP 65)							1		
	Round plug connect	or DIN 41524, 3-pole	(Protection	n class IP 65)							3		
Pressure connections ⁴	Inside thread	5 1/4	fig. 1									0	
	Outside thread	6 1/8 (up to 250 bar)	sealed at f	ront fig. 2								1	
	Outside thread	i 1/4	sealed at f	ront fig. 2								2	
	Outside thread	i 1/2	sealed at f	ront fig. 3								3	
	Outside thread /	/16-20 UNF //_18 NPT	fig. 4									4	
	Outside thread 1	/2-14 NPT	fig. 6									6	
	Outside thread	a 1/8 (up to 250 bar)	sealed at b	oack fig. 7 (NBR)								7	
	Outside thread	i 1/4	sealed at b	back fig. 7 (NBR)								8	
	Outside thread	i 1/2	sealed at b	back fig. 8 (NBR)								9	
Housing material /	Inox												1
Construction	Inox with 0.8 mm pr	essure tip orifice (star	ndard from	100 bar)									3
A	Fomolo estructor D		,										
ACCESSORIES	(IP 65 when installed	and latched)						1	0	R	5	1	0
	Female connector D	IN 43650-A with LED	displav					1	õ	3	5	2	8
	Round plug connect	or (coupling socket) [DIN 41524					1	Ő	3	5	2	4
	Mounting bracket							1	0	4	9	5	4
1.0.1													
² According to ISO stand	on request. ard R 1629, other seal	ing materials on regu	iest.										

³ Without female connector.
 ⁴ Other pressure connections on request.

Dimensions in mm / Electrical connections





EDITION 05/2001

PNP

Electromagnetic compatibility:

CE conformity to EC directive 89/336 EEC (EMC) by application of harmonized standards EN 50081-1, EN 50081-2 and EN 50082-2.

Type of interference/Interference susceptibility	Test standard	Effects
Electrostatic discharge ESD	IEC 1000-4-2 8 kV air discharge / 4 kV contact discharge	No failure (criterion B)
High-frequency electromagnetic radiation (HF)	ENV 50140 10 V/m / 801000 MHz	No effect (criterion A)
Conducted HF interference	ENV 50141 10 V/m / 0.15 80 MHz	No effect (criterion A)
Fast transients (burst)	IEC 801-4 2 kV	No failure (criterion B)
Magnetic fields 50 Hz 30 A/m	EN 61000-4-8	No effect (criterion A)
Type of interference/Emitted interference	<u>Test standard</u>	Effects
Conducted interference Radiation from housing	EN 55022 0.1530 MHz 301000 MHz, 10 meters	None None

Internet: www.hubacontrol.com

NPN

Huba Control Switzerland

Headquaters					
Industriestrasse 17					
CH-54	36 Würenlos				
Phone	e ++41 (0) 56 436 82 00				
Fax	++41 (0) 56 436 82 82				

e-mail: info.ch@hubacontrol.com

Huba Control United Kingdom Unit 19 A Crawley Mill Industrial Estate GB-Witney Oxford OX29 9TJ Phone 01 993 776 667 Fax 01 993 776 671 e-mail: info.uk@hubacontrol.com Huba Control France e-mail: info.fr@hubacontrol.com Huba Control Germany e-mail: info.de@hubacontrol.com Huba Control Netherlands

e-mail: info.nl@hubacontrol.com

Process Instruments

M.R. Štefánika 157/45 017 01 Považská Bystrica Tel./ Fax: 042-4323 946

0905-412 094 0905-412 093

615.05/2001.HUBA/615e0404.DEP.SCHMO/010449.WOH Technical data subject to change.